

INOX | Saladette

SALADETTE ▶ GNI/1 ▶ STAINLESS STEEL TOP

CRX 45A



	GAS R600a	 45 mm	B ENERGY CLASS	4 CLIMATIC CLASS	 38°C

DETAILS

 Curved edge for easy cleaning	 Main switch, digital thermostat and lock fitted as standard	 Anti-condensation "thermal-braker" on door frame
 Inner embossed door design for a better sealing	 Sliding engine room for a manageable after sales servicing	 Inner assistance fan
 Door design		

GENERAL FEATURES

- GNI/1 Refrigerated saladette (STAINLESS STEEL TOP)
- Stainless Steel exterior and interior
- Static Cooling
- Automatic compressor cycle defrost
- Foaming Agent Cyclopentane (45mm per side)
- Digital Thermostat
- Sliding engine room for a manageable after sales servicing
- Plastic thermal-braker as chamber body frame
- Separated plastic water tray
- Front panel tilted holes for better air circulation
- Adjustable shelves GNI/1: 1 Pcs
- Self closing door (New inner embossed design for a better sealing)
- Removable Gasket
- Engine room lock fitted as standard
- N.4 Adjustable feet
- Energy efficiency class: B

TECHNICAL SPECIFICATIONS

Capacity	101 L
Temperature	+0° ~ +8°C
Consumption	1.465 kWh/24h
Rated Power	74 W
Noise level	47 dB(A)
Net Weight	46 Kg
Gross Weight	57 Kg
External Dimensions (WxDxH mm)	450x700x878
Internal Dimensions (WxDxH mm)	359x571x502
Packaging dimensions (WxDxH mm)	500x750x1040
Loading quantities 20'/40'/40'HQ	66/138/138

CERTIFICATION

CE RoHS

PRODUCT DIMENSIONS

